

Product data sheet

SCT 221



Key switch for authorised activation and changing the mode of operation of automatic doors, surface and flush-mounted

AREAS OF APPLICATION

- For authorised activation of automatic doors
- For authorised changing of the mode of operation on automatic doors
- Suitable for exterior and interior use

PRODUCT FEATURES

- Robust metal housing
- Anti-burglar by mechanical security system
- IP rating IP54
- Single-sided switching operation

TECHNICAL DATA

Productname	SCT 221
-------------	---------

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Colour	Dimensions	Type of installation
SCT 221 key switch	One-sided switching operation, without Euro profile half cylinder / One-sided switching operation (key can only be removed in the central position), cover can only be removed with key, light alloy housing, IP rating IP54	054240	silver-coloured	75 x 75 x 11 mm	Flush-mounted installation
SCT 221 key switch	One-sided switching operation, without Euro profile half cylinder / One-sided switching operation (key can only be removed in the central position), cover can only be removed with key, light alloy housing, IP rating IP54	054532	silver-coloured	75 x 75 x 50 mm	Surface-mounted

ACCESSORIES**EURO PROFILE HALF CYLINDER 40 MM**

with Euro profile half cylinder and 3 keys



Designation	Description	Ident-No.	Colour	Type of installation
Euro profile half cylinder 40 mm	Division (10/30) with three keys, keyed to differ, for key switch SCT and MBZ Control cabinet lock	090176	silver-coloured	Integrated