

Product data sheet

Powerturn / Powerturn F roller guide rail



For door leaf installation on the hinge side or opposite hinge side with roller guide rail

AREAS OF APPLICATION

- Reveal depths 0 - 50 mm
- Fire protection doors permitted until reveal depth of 50 mm

Powerturn / Powerturn F roller guide rail



PRODUCT FEATURES

- Opening angle depends on reveal depth
- Compatible with integrated opening restrictor
- Special profile to prevent rollers jumping out

TECHNICAL DATA

Productname	Powerturn / Powerturn F roller guide rail
DIN left	Yes
DIN right	Yes

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Colour	Type of installation
Roller guide rail Powerturn (F)	For door leaf installation opposite hinge side, length 738 mm, lever length 450 mm	153818	EV1	Door leaf installation opposite hinge side
Roller guide rail Powerturn (F)	For door leaf installation hinge side, length 738 mm, lever length 330 mm	153815	EV1	Door leaf installation hinge side
Roller guide rail Powerturn (F)	For door leaf installation hinge side, length 738 mm, lever length 330 mm	153816	according to RAL	Door leaf installation hinge side
Roller guide rail Powerturn (F)	For door leaf installation opposite hinge side, length 738 mm, lever length 450 mm	153819	according to RAL	Door leaf installation opposite hinge side